



MODEL: US4860
US 100ft Superflex
Hose & Hanger Pack

For more information visit

hoselink.com

or call

1-833-216-4673

Cultivating **Connections**

 youtube.com/hoselink



User Manual

MODEL: US4860
US 100ft Superflex
Hose & Hanger Pack

HOSELINK[®]

Kit Contents

- 1 x 100ft Superflex Hose
- 1 x Spray Nozzle and Connector Kit
- 1 x Stainless Steel Hose Hanger
- 1 x Hardware Pack for Stainless Steel Hose Hanger

Superflex Hose Before First Use

- Unroll and stretch the hose out in a long straight line.
- Allow the hose to relax in the sun for a couple of hours.
- Coil the hose neatly into large loops and store on hose hanger for ongoing use.

Precaution

1. FREEZING CONDITIONS

Do not leave the hose in freezing conditions for more than a few occasional hours. If it does freeze, bring it back to above 35°F before next use.

2. HOT CONDITIONS

Do not leave the hose in the sun for extended periods, if not in use. If the hose is to be left in the sun it is best to turn off water at the faucet and release pressure after use. Do not allow the hose to lie on hot surfaces such as driveways or paths for extended periods of time.

3. HOSE CARE

Do not drive your car, lawn mower or any other vehicle over your hose. Do not use the hose or have it come into contact with liquids other than water. Chemicals and corrosive liquids will damage the hose and void the warranty. Maximum water temperature is 100°F.

Hose Hanger Installation

MASONRY INSTALLATION:

- Use a 5/16" drill bit for masonry installation. Drill holes to a depth of 2 inches.
- Once your holes are drilled, gently hammer the plugs into place.

- Using a Phillips-head drill bit, tightly secure the hanger in place with supplied screws.

TIMBER INSTALLATION:

- Drill pilot hole if necessary. Then use a Phillips-head drill bit too tightly secure the hanger in place with supplied screws. Masonry plugs are not required for timber installation.

Warranty

Superflex Hose – 8 Years
Hoselink Fittings – 2 Years
Hose Hanger – 1 Year